

79.01

Elektrodas su rutilo glaistu

UŽKLAUSIMAS

+370 5 23 06 183



Matmenys

Material index	Tipas	d [mm]	L [mm]
790150450ER1466000	ESAB ER.146	5.0	450
790140450ER1466500	ESAB ER.146	4.0	450
790132450ER1466500	ESAB ER.146	3.2	450
790125350ER1465000	ESAB ER.146	2.5	350
790120300ER1464700	ESAB ER.146	2.0	300
790132350OK0465500	ESAB OK.46	3.2	350
790125350OK0465500	ESAB OK.46	2.5	350
790140350OK0465500	ESAB OK.46	4.0	350
790150350OK0465500	ESAB OK.46	5.0	350
790120300OK0462100	ESAB OK.46	2.0	300
790116300OK0461600	ESAB OK.46	1.6	300
790132350LINOM5300	OMNIA 46	3.2	350
790125350LINOM4800	OMNIA 46	2.5	350
790120300LINOM4200	OMNIA 46	2.0	300
790140350LINOM5000	OMNIA 46	4.0	350
790125350LINPA2800	PANTAFIX LINCOLN ELECTRIC	2.5	350
790140350LINPA5400	PANTAFIX LINCOLN ELECTRIC	4.0	350
790132350LINPA4800	PANTAFIX LINCOLN ELECTRIC	3.2	350
790132350RUD104500	RUTWELD 10	3.2	350
790150350RUD104500	RUTWELD 10	5.0	350
790125350RUD104500	RUTWELD 10	2.5	350
790140350RUD104500	RUTWELD 10	4.0	350
790120300RUD101000	RUTWELD 10	2.0	300
790120300RUD122500	RUTWELD 12	2.0	300
790132350RUD125000	RUTWELD 12	3.2	350

Material index	Tipas	d [mm]	L [mm]
790125350RUD12500O	RUTWELD 12	2.5	350
790140450RUD12600O	RUTWELD 12	4.0	450
790150450RUD12600O	RUTWELD 12	5.0	450
790125350EBE310O	SPAWMET EBE	2.5	350
790150450EBE540O	SPAWMET EBE	5.0	450
790140450EBE550O	SPAWMET EBE	4.0	450
790132450EBE560O	SPAWMET EBE	3.2	450
790140350NOREP360O	SPAWMET NORMAL EP	4.0	350
790125350NOREP400O	SPAWMET NORMAL EP	2.5	350
790132450NOREP500O	SPAWMET NORMAL EP	3.2	450
790140450NOREP500O	SPAWMET NORMAL EP	4.0	450
790120300NOREP180O	SPAWMET NORMAL EP	2.0	300
790150450NOREP500O	SPAWMET NORMAL EP	5.0	450
790132350NOREP360O	SPAWMET NORMAL EP	3.2	350
790150450SU46P620O	SPAWMET SUPER 46+	5.0	450
790120300SU46P170O	SPAWMET SUPER 46+	2.0	300
790132350SU46P360O	SPAWMET SUPER 46+	3.2	350
790140450SU46P480O	SPAWMET SUPER 46+	4.0	450
790125350SU46P360O	SPAWMET SUPER 46+	2.5	350
790140350SU46P380O	SPAWMET SUPER 46+	4.0	350
790132450SU46P500O	SPAWMET SUPER 46+	3.2	450